

**(A) Information of the cooker Hood**

	Symbol	Value	Unit
Model identification		CHST60SS	
Annual Energy Consumption	$AEC_{hood}$	75.5	kWh/a
Time increase factor	f	1.7	
Fluid Dynamic Efficiency	$FDE_{hood}$	9.3	
Energy Efficiency Index	$EEl_{hood}$	92.6	
Measured air flow rate at best efficiency point	$Q_{BEP}$	227.7	m <sup>3</sup> /h
Measured air pressure at best efficiency point	$P_{BEP}$	150	Pa
Maximum air flow	$Q_{max}$	427.4	m <sup>3</sup> /h
Measured electric power input at best efficiency point	$W_{BEP}$	102.5	W
Nominal power of the lighting system	$W_L$	18	W
Average illumination of the lighting system on the cooking surface	$E_{middle}$	133	lux
Measured power consumption in standby mode	$P_s$	0	W
Measured power consumption off mode	$P_o$	—	W
Sound power level	$L_{WA}$	Max. 64 / Min. 60	dB

The measurement and calculation method of the above table was done in accordance with commission regulation (EU) No 65/2014 & 66/2014.

**(B) The following shows how to reduce total environmental impact (e.g. energy use) of the cooking process.**

- (1) Install the cooker hood in a proper place where there is efficient ventilation.
- (2) Clean the cooker hood regularly so as not to block the airway.
- (3) Remember to switch off the cooker hood light after cooking.
- (4) Remember to switch off the cooker hood after cooking.

**(C) Information for dismantling.**

Do not dismantle the appliance in a way which is not shown in the user manual. The appliance could not be dismantled by user. At the end of life, the appliance should not be disposed of with household waste. Check with you Local Authority or retainer for recycling advice.